

**UNMATCHED
HIGH DEFINITION
CLARITY AND
USABILITY.**



Revolutionise the way you present and collaborate.

Unleash the potential of your presentations with Epson EB-L260F/L210W series projectors! Elevate your visuals to a whole new level with brilliantly vivid and crystal-clear images. Designed specifically for the education and corporate sectors, these projectors optimise your content on immersive Full HD displays with expansive wide-aspect screens. Whether you're in a conference room or a spacious lecture hall, captivate your audience, fuel their engagement, and make a lasting impression.

HEAD OFFICE, KARACHI: Safety pride, CL-7/18/16 Opp. F.G. Public School Dr. Daud Pota Road Karachi, **LAHORE:** 401, 403 4th Floor Eden Towers Main Boulevard Gulberg-III Lahore, **ISLAMABAD:** Mezzanine Floor, Plot No. MC-33, Sector 5, Main Commercial Road, Ghouri Town Phase-5 Islamabad, **HYDERABAD:** F23 Mezzanine Floor, Shelter Shopping Mall Sadler Hyderabad.

Contact Us: Karachi: Sales@abmds.net ; Lahore: Sales.lhr@abmds.net ; Islamabad: Sales.isb@abmds.net ; Hyderabad: Sales.hyd@abmds.net

0300-2008866

SPECIFICATIONS

MODEL NUMBER		EB-L260F
SKU Number		V11HA69080
Projection Technology		RGB liquid crystal shutter projection system
Specifications of Main Parts		
LCD	Size	0.62" (C2Fine)
	Resolution	Full HD (1080p) (1920 x 1080)
Projection Lens	Aspect Ratio Screen	21:9
	Type	Optical Zoom (Manual) / Focus (Manual)
	F-Number	1.51 – 1.77
	Focal Length	18.2 – 29.1mm
	Zoom Ratio	1.0 – 1.62 (Optical Zoom)
Light Source	Throw Ratio	1.32 – 2.12
	Type	Laser Diode
Life (Normal / Quiet / Extended)		20,000 / 20,000 / 30,000 hrs
Screen Size (Projected Distance)		Standard: 62" screen @ 180cm Zoom (Wide): 31" to 310" screen (88 – 906cm)
Brightness¹		
White Light Output (Normal / Eco)		4,600lm / 3,200lm
Colour Light Output		4,600lm
Contrast Ratio		Over 5,000,000:1
Internal Speaker(s)		
Sound Output		16W Monaural
Geometric Correction		
Vertical / Horizontal Keystone		±30° / ±30°
Quick Corner		Yes (Manual)
Image		
Noise Reduction		Yes
Super-Resolution		Yes
Detail Enhancement		Yes
Connectivity		
Analog Input	D-Sub 15Pin	2
	Composite	RCA x 1 (Yellow)
Digital Input	HDMI	2 (HDCP 2.3)
Analog Output	D-Sub 15Pin	1 (Black) (in common with Computer 2)
Audio Input	RCA	1 (White, Red)
	Stereo Mini Jack	2
Audio Output	Stereo Mini Jack	1
Others	USB Type A	1 (For PC Free, FW Update, Copy OSD Settings or 5V/2A Power Supply)
	USB Type B	1 (For Firmware Update, Copy OSD Settings)
Control IO	Mic IO	Stereo Mini x 1
Network	RS-232C	D-Sub 9pin x 1
	Wired LAN	RJ45 x 1 (100Mbps)
Wireless		Built-in and Optional (Using ELPAP11)
Wireless Specification		
(Wireless LAN and Screen Mirroring)		
Supported Speed For Each Mode	Infrastructure: IEEE 802.11b (2.4GHz): 11Mbps ² , IEEE 802.11g (2.4GHz): 54Mbps ² , IEEE 802.11n (2.4GHz): 72.2Mbps ² , IEEE 802.11a (5GHz): 54Mbps ² , IEEE 802.11n (5GHz): 150Mbps ² , IEEE 802.11ac (5GHz): 325Mbps ² Access Point (Wi-Fi Direct): IEEE 802.11g (2.4GHz): 54Mbps ² , IEEE 802.11n (2.4GHz): 72.2Mbps ² , IEEE 802.11a (5GHz): 54Mbps ² , IEEE 802.11n (5GHz): 150Mbps ² , IEEE 802.11ac (5GHz): 325Mbps ²	
Supported Mode	Infrastructure, Access Point (Wi-Fi Direct)	
Wireless LAN Security	Infrastructure: OPEN, WPA2 / WPA3-PSK, WPA2 / WPA3-EAP Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS, EAP-Fast ; Access Point (Wi-Fi Direct): WPA2-PSK (AES)	
(Optional Wireless LAN)		
Supported Speed For Each Mode	Access Point (Wi-Fi Direct): IEEE 802.11g (2.4GHz): 54Mbps ² , IEEE 802.11n (2.4GHz): 72.2Mbps ² , IEEE 802.11a (5GHz): 54Mbps ² , IEEE 802.11n (5GHz): 150Mbps ² , IEEE 802.11ac (5GHz): 325Mbps ²	
Supported Mode	Access Point (Wi-Fi Direct)	
Wireless LAN Security	WPA2-PSK (AES)	
Operating Temperature³		
0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F - 104 °F] ; 20% to 80% Humidity, No Condensation Over 2,286 m (7,500 ft): 0 - 35 °C [32 °F - 95 °F] ; 20%-80% Humidity, No Condensation		
Operating Altitude		
Over 1,500 m / 4,921 ft, with High Altitude Mode: 0 - 3,048 m (0 - 10,000 ft)		
Direct Power On / Off		
Yes		
Start-Up Period		
Less than 9 seconds (Epson Logo), Warm-up Period: 30 seconds		
Quick Start-Up		
Less than 5 seconds (Display)		
Cool Down Period		
Instant Off		
Air Filter	Type	Electrostatic Filter
	Maintenance Cycle ⁴	20,000 hours
Power Supply Voltage		
100 – 240 V AC ±10%, 50/60 Hz		
Power Consumption (220 - 240V)		
Lamp On (Normal / Extended)		260W / 191W
Standby (Network On / Off)		2.0W / 0.5W
Dimension Excluding Feet (D x W x H)		
299 x 325 x 90 mm		
Weight (with cable cover)		Approx. 4.2kg
Fan Noise (Normal / Eco)		37dB / 27dB

HEAD OFFICE, KARACHI: Safety pride, CL-7/18/16 Opp. F.G. Public School Dr. Daud Pota Road Karachi, **LAHORE:** 401, 403 4th Floor Eden Towers Main Boulevard Gulberg-III Lahore, **ISLAMABAD:** Mezzanine Floor, Plot No. MC-33, Sector 5, Main Commercial Road, Ghouri Town Phase-5 Islamabad, **HYDERABAD:** F23 Mezzanine Floor, Shelter Shopping Mall Sadler Hyderabad.

Contact Us: Karachi: Sales@abmds.net ; Lahore: Sales.lhr@abmds.net ; Islamabad: Sales.isb@abmds.net ; Hyderabad: Sales.hyd@abmds.net

📞 0300-200886